

Battery-Operated Friction-weld

The BXT2 combination tool applies polypropylene or polyester strapping, utilizing friction weld joint technology to join the strap ends. An automatic weld function speeds up cycle time.

Used together, the PT tensioner and BTS sealer are ideal for tensioning and joining strap ends in outdoor or harsh environments.



BXT2-16, BXT2-19



BTS-16, 19, 25, 32*



PT*

Model	Part Number	Strap Type Contrax, Tenax	Joint Type	Applied Tension	Description	Shipping Weight	
						lbs	kg
BXT2-16	428340	9-13 mm Contrax & Tenax	Friction-weld	Up to 550 lbs	Battery	9	4.1
BXT2-19	428350	1816, 1818, 1822 (with Guide change); 816, 818, 2030, 2040, 2040H				Up to 880 lbs	9.3
BTS-16/PT-16 COMBO	427100	2030, 2040, 2220, 2225, 2480, 10050	Friction-weld	Up to 800 lbs.	Battery	(BTS) 6.8	3
BTS-19/PT-19 COMBO	427101						
BTS-25/PT-25 COMBO	427102						
BTS-32/PT-32 COMBO	428220						

* The BTS and PT tools can be ordered separately.

Dispensers

For plastic strapping



DD-1A
Floor model with straproller. Can be suspended overhead.



DF-16A
Designed for use with polyester strapping.



DF-1-12D
For power equipment. Dancer arm and brake. Base sold separately (Part No. 024360).



PSD-109
For power equipment. Available in left or right-handed models.



DO-3D
Can be suspended from a wall or ceiling.

Strap Dispenser Model	Part Number	Strap Size		Straproller	Portable	Tool Tray	Dimensions						Dispenser Weight	
		inch	mm				Height		Width		Length		lbs	kg
							inch	mm	inch	mm	inch	mm		
DD-1A	024520	7/16-1/2	10.5-12	•	•	•	41	1 041	12	305	25	635	48	22
DF-16A	422300	3/8-3/4	9-19.0		•	•	38	965	18	457	28-1/2	724	62	28
DF-1-12D	031318	3/8-3/4	9-19.0				36-3/4	933	12-1/2	315	47-1/4	1200	97	44
PSD-109	480171 Left-hand	3/8-3/4	9-19.0				44-1/2	1 130	15	380	38-3/8	975	126	57
	480172 Right-hand													
DO-3D	024500	3/8-3/4	9-19.0	•			31	787	6-3/4	171	27-3/4	705	41	19

Pneumatic accessories See page 11 for additional fittings.



A filter-regulator-lubricator (FRL) assembly (Part No. 429141, with hose) or (Part No. 429130, without hose) is needed with all pneumatic tools. Additional fittings and air hoses are available from Signode to help provide optimum operation. Please contact your local Signode sales representative for more information on the proper fittings for your specific tool.

Recommended air hose for pneumatic tools: 10' x 1/2" (3.0m x 12mm) i.d. (Part No. 429145).

Note: Use lightweight, non-detergent oil in lubricator, such as Non-Fluid Oil No. LS-1236 (Part No. 008556) or equivalent.